

4-Unit 10/100 Passive Tap (10/100-PTX4)



Get the functionality of four 10/100 taps in a 1U chassis.

The 10/100-PTX4 Four-Unit Passive Tap provides simple 24 x 7 passive access to your 10/100 Ethernet segments and is an ideal solution for full-time monitoring applications.

These passive taps from Datacom Systems feature industry-leading, "no break the link" design, so network traffic will continue to flow uninterrupted even if power is lost to the tap.

Dual redundant power supplies maximize monitoring uptime.

- Permanent In-Line access to Ethernet links - eliminates the need for network connectors to be disconnected and connected each time a segment needs to be analyzed
- Won't break the network link even if power is lost to the tap, eliminating packet loss and network delays
- Enables viewing of ALL seven layers of network traffic and passes all pairs
- Space-saving design - Four (4) 10/100 passive taps in an easy to install 1U chassis (fits a standard 19" rack)
- Ideal for Security and Monitoring applications - non-intrusive and invisible to the network
- Monitor both sides of a full-duplex conversation
- Supports Power over Ethernet (PoE)
- Redundant internal power supplies insure seamless monitoring even if the main power source is unavailable

TECHNICAL SPECIFICATIONS

Network Ports

- Four (4) 10/100 Taps (RJ45) Network Connections
- Four (4) 10/100 (RJ45) Tap/Monitoring Connections

Power Requirements

- Dual Redundant Power Supplies

Physical Dimensions (H x W x D)

- 1.75 x 19 x 11 in.
- 4.45 x 48.26 x 27.94 cm.

Weight

- 12 lbs.
- 5.45 Kgs

Environmental

- Operating Temperature: 0° to 40° C
- Storage Temperature: 30° to 65° C
- Humidity: Less than 95° C non-condensing

Warranty

- 2-year limited warranty

Ordering Information

Product	Description
10/100-PTX4	4-Unit 10/100 Passive Tap (four taps)

ACCESS YOUR NETWORK™

Contact NextGig Systems 805-277-2400 NextGigSystems.com