



Optional 3-Unit (19 Inch) Rack Mount

The F50/50/62-2LCM Dual Fiber Passive TAP provides permanent access into two multi-mode fiber links. This network TAP is ideal for security applications, network monitoring and anywhere you need to see all the data that only an In-Line solution can provide. Invisible to the network and non-powered, fiber TAPs will not affect network performance or integrity.

- Passive, non-powered design
- Two TAPs allow you to connect to one tool per link; tools require a dual NIC card to receive both sides of the conversation
- Supports multiple topologies, including Gigabit Ethernet, ATM, OC3-OC48 and SONET
- View layer 1 and 2 errors not seen when performing network monitoring using SPAN ports
- Available with custom split ratios upon request
- Space saving design allows you to TAP up to four links in 1U

TECHNICAL SPECIFICATIONS

TAP Connections

Two Links Tapped Dual LC

Monitor Ports

Two Tools Dual LC

Split Ratio

50/50

Additional Split Ratios Available

Insertion Loss

4.0 dB Insertion Loss Max.

Physical Dimensions (HxWxD)

1.13 x 5.75 x 5.63 in (2.86 x 14.61 x 14.29 cm)

Weight

0.75 lbs (0.34 kgs)

Environmental

Operating Temperature: 32° to 104°F (0° to 40°C)

Storage Temperature: -22° to 149°F (-30° to 65°C)

Humidity: 5 to 95° non-condensing

Warranty

Two (2) Year Limited Warranty

Order Information

Product	Description
F50/50/62-2LCM	Dual Fiber Passive TAP OC3-OC48, 1000SX (62.5 micron) 50/50 Split Ratio w/LC Connectors
RMC-3	3 Tap 1U Rack Mount Chassis

ACCESS YOUR NETWORK™

Contact NextGig Systems 805-277-2400 NextGigSystems.com