



Eliminate clutter and organize your power connections with the Datacom Systems Multi-Unit Power Supply.

This easy to manage 1U power supply contains two (2) redundant hot-swappable power supplies and contains 12 lead power connections to provide dual redundant power for up to 12 Datacom Systems network taps or aggregators. Each power lead delivers up to 3 amps.

Includes cabling for 12 redundant device connections and DC power cords for devices located within 5U of the power supply.

- Powers up to 12 redundant power connections
- Easy to connect with included cabling set
- Universal power for global deployment
- Fits a standard 19" rack mount
- LEDs on hot-swappable power supplies confirm power status
- Compatible with Datacom Systems DC-powered units
- Fully RoHS compliant

TECHNICAL SPECIFICATIONS

Connectors

24 - 5.0 VDC 3.0 A Receptacles

Power Consumption Watts

480.0

BTU/h

1636.8

Electrical Specifications

Output: 405-72.0VDC; 10.05-5.0A

Certifications

CE

Physical Dimensions (HxWxD)

1.75 x 19.00 x 13.00 in (4.45 x 48.26 x 33.02 cm)

Weight

10.0 lbs (4.54 kgs)

Environment

Operating Temperature: 32° to 104°F (0° to 40°C) Storage Temperature: -22° to 149°F (-30° to 65°C)

Humidity: 5 to 90% non-condensing

Warranty

Two (2) Year Limited Warranty

Order Information

Product Description

RPS-12-5-DC Dual Redundant

Rack Mountable DC

Power Supply

ACCESS YOUR NETWORK™